

# 8G30H

## SPECIFICATIONS

Nominal Voltage (V)	12V
Capacity at C/100	108Ah
Weight	71.7 Lbs. (32.5 kg)
Plate Alloy	Lead Calcium
Posts	Forged terminals & bushings
Container/Cover	Polypropylene
Operating Temperature Range	-76°F (-60°C) – 140°F (60°C)
Charge Voltage @ 68°F (20°C)	
Cycle	2.30 - 2.35 VPC
Float	2.25 - 2.30 VPC
Vent	Self-sealing (2 PSI operation)
Electrolyte	Sulfuric acid thixotropic gel
Resistance	4.0 Milliohms (full charge)
Terminal	T876

Rated non-spillable by ICAO, IATA and DOT  
Approved by CEC

Made in the U.S.A by East Penn Manufacturing

Distributed by:


Valve-Regulated, Gelled-Electrolyte Battery



## DIMENSIONS

Length (mm)	12.94 (329 mm)
Width (mm)	6.75 (171 mm)
Height (mm)	9.75 (248 mm)

## Cycling Ability



Number of cycles vs. depth of discharge  
at +20°C  
discharge with 20 hour rate

## MK Battery

1645 South Sinclair Street • Anaheim, California 92806  
Toll Free: 800-372-9253 • Fax: 714-937-0818 • E-Mail: sales@mkbattery.com

